



CORE ONE

TECHNOLOGY: **TRUE ON LINE Double Conversion**
CLASSIFICATION: **VFI-SS-111** (EN 62040-3)
POWER RANGE: **2 - 3 kVA**
No. OF PHASES: **1:1**



■ APPLICATIONS

- Servers
- Working stations
- Lighting
- Laboratory equipment
- Security systems
- Automation and control systems

■ SPECIFICATION

Technology True On-Line Double Conversion Technology provides perfect output voltage parameters, regardless of the input voltage and the load.

Automatic bypass provides continuous load supply in critical conditions, such as overheating or inverter failure.

Communication:

- **USB, RS232** for UPS and load supervision and control.
- **TVSS** to protect tele information equipment.
- **Smart slot** allows connect SNMP card to manage UPS throw network or AS400 card with potential free contactors.

LCD control panel displays UPS and power parameters as well as hundreds of useful information.

Small dimensions only 2U for 2,3 kVA provides minimum space in rack to install.

High efficiency up to 93% in online mode to minimizes energy consumption and reduces heat emissions, which makes cooling of rooms cheaper.

ECO-Mode allows 99% efficiency and additional energy savings.

CVCF Frequency converter mode allows UPF to operate in the 50 Hz or 60 Hz to supply non-standard receivers.

Automatic diagnostics guarantee full device performance, control of components and operating parameters without user intervention.

The high value of input power factor restricts the current value of the device from professional network.

Wide input voltage range for normal mode ensures that batteries are used only if necessary – in fact, only when the input voltage is completely lost.

12A and 8A battery charger for 2,3kVA unit gives ability to connect high capacity batteries for long autonomy.

The ability to extend the backup time by adding battery modules allows you to precisely adjust the required autonomy time.

The high output power factor PF=1 for 2,3 kVA guarantees up to 30% more active power compared to other power supplies in this class.

Wide input frequency range for normal mode makes possible to freely use the power supply in a mixed network of city-generator.

Auto restart guarantees maintenance-free operation in case of long power failure.

Cold start provides possibility to launch UPS without main voltage.

Advanced battery management guarantees optimum battery charging and usage. The 3-stage charging process extends their service life up to 50% and reduces operating costs.

Excellent voltage quality achieved by using the IGBT (3L) inverter and high frequency PWM modulation ensures that the voltage is delivered in extremely stable parameters, regardless of power interference and the type of power supply.

Overload resistance is reliable power supply with transient states and high fault tolerance.

Advanced software gives the user complete control over the device and the power receivers.

EPO connector provides the ability to remotely switch off the power supply in the case of fire.

Programmable output sockets allows you to manage the presence of output voltage during battery operation.



CORE ONE

Model	CORE ONE 2K	CORE ONE 3K
Power	2000 VA/ 2000 W	3000 VA/ 3000 W
No. Of phases IN : OUT	1:1	
Input		
Nominal voltage	208 / 220 / 230 / 240 VAC	
Voltage range	-52% ÷ +30%	
Frequency	50 / 60 Hz	
Frequency range	-20% ÷ +20%	
THDi	<3%	
Input power factor	≥0,99	
Output		
Nominal voltage	208 / 220 / 230 / 240 VAC	
Output power factor	1,0	
Voltage regulation static/dynamic	±1% / ±3%	
Frequency	50 / 60 Hz ± 0,05 Hz	
Overload capacity inverter	110% - no limit, 130% - 5 min., 140% - 30 sec., >140% - 1,5 sec.	
Efficiency On-Line mode	>93%	
Efficiency Eco mode	99%	
Controlled socket groups – with programmable power off	1 x 4 psc.	
Type and number of sockets	IEC320-C13 x 8	IEC320-C13 x 8 and IEC320-C19 x 1
Terminal board	n/a (Plug&Play)	
Creast factor	3:1	
Batteries		
Amount of internal batteries	4 x 7/9 Ah	6 x 7/9 Ah
Cold start	Yes	
Connector for external batteries	Yes	
Charging time	4 hours up to 90% of capacity (configurable)	
Charger	1-12A	1-8A
Weight and dimensions		
Dimensions and weight of UPS (W x D x H)	438 x 510 x 88 (2U)	438 x 630 x 88 (2U)
	19,5 kg	27,5 kg
Dimensions and weight of battery module (W x D x H)	438 x 510 x 88 (2U)	438 x 630 x 88 (2U)
	28,5 kg	40,8 kg
Communications		
Working indicator	LCD + indicators LED, alarm sound alarm	
Communications	Standard: USB, RS232, TVSS, Smart slot, REPO Options: AS400 card, SNMP card	
Environmental		
Noise level	<48 dB	
Operating temperature for UPS	0°C ÷ 40°C	
Recommended operating temperature for UPS	15°C ÷ 25°C	
Storage temperature	-25°C ÷ 55°C	
Humidity	0 ÷ 95% (without condensing)	
Certification		
Standards	EN 62040-2:2005, EN 62040-2:2006	
Safety	IEC62040-1-1, CE, 62040-3 :2001	
Options		
- SNMP card - Environmental sensor (EMD) - Maintenance bypass - REPO	- AS400 card - Additional battery module - Rail kits 19" - output plug fixing part	